

CARTRIDGE FILTERS

CARTRIDGE FILTERS

RTL CARTRIDGE FILTERS

RTL toploaded cartridge filter made in ABS plastic. The filter has a built-in by-pass.
Max water temperature 45° C. Max water pressure 2,0 bar.

| Size | RTL25 | RTL50 | RTL75 |
|------------------------------------|----------|----------|----------|
| Filter area m ² / sq.ft | 2,3 / 25 | 4,6 / 50 | 6,9 / 75 |
| Max flow m ³ / hour | 6 | 12 | 18 |
| Pipe connection | 50 mm. | 50 mm. | 50 mm. |
| Measurement | | | |
| Height mm | 500 | 500 | 670 |
| Diameter mm | 210 | 210 | 210 |

| Part number | Spare part number | | |
|-------------------------------------|-------------------|-------------------|-------------------|
| RTL cartridge filter | 2,3m ² | 4,6m ² | 6,9m ² |
| 01. Lockring for lid. | 49-600001 | 49-600001 | 49-600001 |
| 02. Air screw kit. | 49-310002 | 49-310002 | 49-310002 |
| 03. O-ring for air screw. | - | - | - |
| 05. O-ring for filter. | 49-600005 | 49-600005 | 49-600005 |
| 06. Filter. | 48-709023 | 48-709046 | 48-709069 |
| 07. Screw for lock. | 49-600007 | 49-600007 | 49-600007 |
| 08. Lock. | 49-600008 | 49-600008 | 49-600008 |
| 11. Base for filter. | 41-700010 | 41-700010 | 41-700010 |
| 12. Complete lid with pos. 2-3-4-5. | 49-600012 | 49-600012 | 49-600012 |
| Adaptor 2"x 50mm for glue. | 41-170234 | 41-170234 | 41-170234 |

